



Standard Features

- Aluminum frame, Cover and Type 304 SS Fan Guards
- Built-In 0-100°F adjustable thermostat
- Standard line cord
- Integral Condensate Drip Pan (vertical orientation)
- Environmentally Friendly - No CFC's, Oils or Gases
- No Maintenance
- Mounts and operates vertically or horizontally
- 12 month warranty
- Made in the USA

Included

- Installation and Operation Manual
- Mounting gasket
- Stainless Steel Mounting Hardware

Standard Voltages

220VAC 50/60 Hz

Model #	Available Voltage	Input Voltage Range	Current	Heating Capability	Mounting Flange Dimensions	Certification	Weight	Mounting
AAC-161B-4XT	220VAC	180 - 264 V	8.9 A	N/A	23.5" H x 19.526" W	N/A	94 LBS.	N/A
AAC-161B-4XT-HC	220VAC	180 - 264 V	8.9 A	800 watts	23.5" H x 19.526" W	N/A	94 LBS.	N/A

NEMA Rating:	4X
Cooling T-Stat set range:	0-100°F
T-Stat Accuracy:	±1°F
T-Stat Hysteresis:	4F
Heating T-stat set point:	ON @ 45F, OFF @ 55F
Cold-side airflow:	220 cfm
Hot-side airflow:	360 cfm
Operating temperature:	-4 to 140 °F
Storage temperature:	-4 to 194 °F
Warranty:	12 months

Optional Equipment

- Condensate drip pan (horizontal)
- Rain Shroud (vertical and horizontal)
- Extension Frame
- Digital Temperature Controller
- Black Epoxy Coating
- Extended Warranty

Customizations

- Stainless Steel Construction for Extreme Environments
- Custom color finish
- Increased heating capability
- Non-standard Mounting Configurations
- And More - Please inquire for details*

3500 BTU - 161B SERIES

THERMOELECTRIC AIR CONDITIONER

AAC-161B Performance Chart

