



Standard Features

- Aluminum frame, Cover and Type 304 SS Fan Guards
- Built-In 0-100° adjustable thermostat
- NEMA 5-15 Plug on 120VAC units
- Standard line cord for other voltages
- Integral Condensate Drip Pan (vertical orientation)
- Environmentally Friendly - No CFC's, Oils or Gases
- No Maintenance
- Mounts and operates vertically or horizontally
- 12 month warranty
- Made in the USA
- CE Certified **CE**

Included

- Installation and Operation Manual
- Mounting gasket
- Stainless Steel Mounting Hardware

Standard Voltages

- 120VAC 50/60 Hz
- 240VAC 50/60 Hz

Model #	Available Voltage	Input Voltage Range	Current	Heating Capability	Mounting Flange Dimensions	Certification	Weight	Mounting
AAC-151B-4XT	120-240VAC	100-264VAC	11.8 - 6.3 A	N/A	23.5" H x 19.526" W	CE	72 LBS	N/A
AAC-151B-4XT-HC	120-240VAC	100-264VAC	11.8 - 6.3 A	800 WATTS	23.5" H x 19.526" W	CE	72 LBS	N/A

2500 BTU - 151B SERIES

THERMOELECTRIC AIR CONDITIONER

NEMA Rating:	4X
Cooling T-Stat set range:	0-100°F
T-Stat Accuracy:	±1°F
T-Stat Hysteresis:	4F
Heating T-stat set point:	ON @ 45F, OFF @ 55F
Cold-side airflow:	180 cfm
Hot-side airflow:	250 cfm
Operating temperature:	-4 to 140 °F
Storage temperature:	-4 to 185°F
Warranty:	12 months

Optional Equipment

- Rain Shroud (vertical and horizontal)
- Digital Temperature Controller
- Black Epoxy Coating
- Extension Frame
- Extended Warranty

Customizations

- Stainless Steel Construction for Extreme Environments
 - Custom color finish
 - Increased heating capability
 - Non-standard Mounting configurations
- And More - Please inquire for details*

AAC-151B Performance Chart

