



Standard Features

- 430-560 BTU/HR Cooling
- Type 304 Stainless Steel frame, Cover and Fan Guards
- Built-In 0-100° adjustable thermostat
- NEMA 5-15 Plug on 120VAC units
- Standard line cord for other voltages
- Environmentally Friendly - No CFC's, Oils or Gases
- No Maintenance
- Mounts and operates vertically or horizontally
- 12 month warranty
- Made in the USA
- UL Listed

Included

- Installation and Operation Manual
- Mounting gasket
- Stainless Steel Mounting Hardware
- Horizontal Condensate Drip Pan

Standard Voltages

120/240VAC 50/60Hz

Model #	Available Voltage	Input Voltage Range	Current	Heating Capability	Mounting Flange Dimensions	Certification	Weight	Mounting
AAC-140C-4XT	120/240VAC	95 - 264 V	1.8 A, 0.9 A	N/A	12" H X 6" W	cULus 1995 Listed	18 LBS.	N/A
AAC-140C-4XT-HC	120/240VAC	95 - 264 V	1.8 A, 0.9 A	100 WATTS	12" H X 6" W	cULus 1995 Listed	18 LBS.	N/A

400 BTU - 140C SERIES

THERMOELECTRIC AIR CONDITIONER

NEMA Rating:	4X
Cooling T-Stat set range:	0-100°F
T-Stat Accuracy:	±1°F
T-Stat Hysteresis:	4°F
Heating T-stat set point:	ON @ 45F, OFF @ 55F
Cold-side airflow:	26 cfm
Hot-side airflow:	40 cfm
Operating temperature:	-4 to 140 °F
Storage temperature:	-30°C to 70°C/ -22°F to 158°F
Warranty:	12 months

Optional Equipment

- Extension Frame
- Rain Shroud
- Digital Temperature Controller
- Recessed Frame
- Extended Warranty

Customizations

- Type 316 SS Construction for extreme environments
 - Custom color finish
 - Increased heating capability
 - Non-standard Mounting configurations
- And More - Please inquire for details*



AAC-140C Performance Chart

