



Standard Features

- 800-950 BTU/Hr
- Type 304 Stainless Steel Frame, Cover and Fan Guards
- Built-In 0-100° adjustable thermostat
- Environmentally Friendly - No CFC's, Oils or Gases
- No Maintenance
- Mounts and operates vertically or horizontally
- 12 month warranty
- Made in the USA

Included

Installation and Operation Manual
Mounting gasket
Stainless Steel Mounting Hardware

Standard Voltages

110-240 VAC Power
(DC Voltages Optional)

Model #	Available Voltage	Input Voltage Range	Current	Heating Capability	Mounting Flange Dimensions	Certification	Weight	Mounting
AAC-141A-4XT	110-240VAC	95-264VAC	3.5-1.8 A	N/A	13" H X 13" W	cULus 1995 Listed	30 LBS.	N/A
AAC-141A-4XT-HC	110-240VAC	95-264VAC	3.5-1.8 A	200 WATTS	13" H X 13" W	cULus 1995 Listed	30 LBS.	N/A
AAC-141A-4XT-NF	110-240VAC	95-264VAC	3.5-1.8 A	N/A	13" H X 12" W	cULus 1995 Listed	30 LBS.	N/A
AAC-141A-4XT-HC-NF	110-240VAC	95-264VAC	3.5-1.8 A	200 WATTS	13" H X 12" W	cULus 1995 Listed	30 LBS.	N/A
AAC-141A-4XT-M04	24VDC	23-26VDC	15 A	N/A	13" H X 13" W	N/A	30 LBS.	N/A
AAC-141A-4XT-HC-M04	24VDC	23-26VDC	15 A	200 WATTS	13" H X 13" W	N/A	30 LBS.	N/A
AAC-141A-4XT-NF-M04	24VDC	23-26VDC	15 A	N/A	13" H X 12" W	N/A	30 LBS.	N/A
AAC-141A-4XT-HC-NF-M04	24VDC	23-26VDC	15 A	200 WATTS	13" H X 12" W	N/A	30 LBS.	N/A

ThermoTEC™ 141A Series - 800 BTU

THERMOELECTRIC AIR CONDITIONER

NEMA Rating:	4X
Cooling T-Stat set range:	0-100°F
T-Stat Accuracy:	±1.0°F
T-Stat Hysteresis:	4F
Heating T-stat set point:	On at 45°F Off at 55°F
Cold-side airflow:	50 cfm
Hot-side airflow:	95 cfm
Operating temperature:	-4 to 140 °F
Storage temperature:	-4 to 185 °F
Warranty:	12 months

Optional Equipment

- Vertical Condensate Drip Pan
- Extension Frame
- Rain Shroud
- Digital Temperature Controller
- Recessed Frame
- Extended Warranty

Customizations

- Type 316 SS Construction for extreme environments
- Custom color finish
- DC options available
- Non-standard Mounting configurations
- And More – Please inquire for details



AAC-141A Performance Chart

