



## Standard Features

- 1500-2200 BTU/Hr
- Aluminum frame and Cover and Type 304 Stainless Steel Fan Guards
- UL Listed
- Built-In 0-100° adjustable thermostat
- Environmentally Friendly - No CFC's, Oils or Gases
- No Maintenance
- Integral condensate drip pan (vertical mount only)
- 12 month warranty
- Made in the USA

## Included

- Installation and Operation Manual
- Mounting gasket
- Stainless Steel Mounting Hardware

## Standard Voltages

- 110-240 VAC Power
- (DC Voltages Optional)

Model #	Available Voltage	Input Voltage Range	Current	Heating Capability	Mounting Flange Dimensions	Certification	Weight	Mounting
<a href="#">AAC-145A-4XT-M34</a>	120-240 VAC	100-264 V	6.0 A, 4.0 A	N/A	12" H X 19.625" W	N/A	47 LBS.	Vertical Only
<a href="#">AAC-145A-4XT-HC-M34</a>	120-240 VAC	100-264 V	6.0 A, 4.0 A	400 WATTS	12" H X 19.625" W	N/A	47 LBS.	Vertical Only
<a href="#">AAC-145A-4XT-M34/04</a>	24 VDC	23-26 V	30 A	N/A	12" H X 19.625" W	N/A	47 LBS.	Vertical Only
<a href="#">AAC-145A-4XT-HC-M34/04</a>	24 VDC	23-26 V	30 A	400 WATTS	12" H X 19.625" W	N/A	47 LBS.	Vertical Only

# 1500 BTU - 145A-M34 SERIES

## THERMOELECTRIC AIR CONDITIONER

<b>NEMA Rating:</b>	4X
<b>Cooling T-Stat set range:</b>	0-100°F
<b>T-Stat Accuracy:</b>	±1°F
<b>T-Stat Hysteresis:</b>	4F
<b>Heating T-stat set point:</b>	ON @ 45F, OFF @ 55F
<b>Cold-side airflow:</b>	95 cfm
<b>Hot-side airflow:</b>	140 cfm
<b>Operating temperature:</b>	-4 to 140 °F
<b>Storage temperature:</b>	-4 to 185 °F
<b>Warranty:</b>	12 months

### Optional Equipment

- Military-Spec Fans
- Extension Frame
- Rain Shroud
- Digital Temperature Controller
- Extended Warranty

### Customizations

- 304 or 316 Stainless steel Construction for extreme environments
- Custom color finish
- Increased heating capability
- DC Voltages Available
- Non-standard Mounting configurations
- And More - Please inquire for details*

