



### Standard Features

- 1500-2200 BTU/Hr
- Type 304 Stainless Steel frame, Cover and Fan Guards
- UL Listed
- Built-In 0-100° adjustable thermostat
- Environmentally Friendly - No CFC's, Oils or Gases
- No Maintenance
- Mounts and operates vertically or horizontally
- 12 month warranty
- Made in the USA

### Included

- Installation and Operation Manual
- Mounting gasket
- Stainless Steel Mounting Hardware
- Horizontal Drip Pan

### Standard Voltages

- 110-240 VAC Power
- (DC Voltages Optional)

Model #	Available Voltage	Input Voltage Range	Current	Heating Capability	Mounting Flange Dimensions	Certification	Weight
AAC-145A-4XT	120-240 VAC	100-264 V	6.0 A, 4.0 A	N/A	20.25" H X 13" W	cULus	55 LBS.
AAC-145A-4XT-NF	120-240 VAC	100-264 V	6.0 A, 4.0 A	N/A	20.25" H X 12" W	cULus	55 LBS.
AAC-145A-4XT-HC	120-240 VAC	100-264 V	6.0 A, 4.0 A	400 WATTS	20.25" H X 13" W	cULus	55 LBS.
AAC-145A-4XT-HC-NF	120-240 VAC	100-264 V	6.0 A, 4.0 A	400 WATTS	20.25" H X 12" W	cULus	55 LBS.
AAC-145A-4XT-M04	24 VDC	23-26 V	30 A	N/A	20.25" H X 13" W	N/A	55 LBS.
AAC-145A-4XT-NF-M04	24 VDC	23-26 V	30 A	N/A	20.25" H X 12" W	N/A	55 LBS.
AAC-145A-4XT-HC-M04	24 VDC	23-26 V	30 A	400 WATTS	20.25" H X 13" W	N/A	55 LBS.
AAC-145A-4XT-HC-NF-M04	24 VDC	23-26 V	30 A	400 WATTS	20.25" H X 12" W	N/A	55 LBS.

# 1500 BTU - 145A SERIES

## THERMOELECTRIC AIR CONDITIONER

NEMA Rating:	4X
Cooling T-Stat set range:	0-100°F
T-Stat Accuracy:	±1°F
T-Stat Hysteresis:	4F
Heating T-stat set point:	ON @ 45F, OFF @ 55F
Cold-side airflow:	95 cfm
Hot-side airflow:	140 cfm
Operating temperature:	-4 to 140 °F
Storage temperature:	-4 to 185 °F
Warranty:	12 months

### Optional Equipment

- Vertical Condensate Drip Pan
- Extension Frame
- Rain Shroud
- Digital Temperature Controller
- Recessed Frame
- Extended Warranty

### Customizations

- Type 316 SS Construction for extreme environments
  - Custom color finish
  - Increased heating capability
  - DC Voltages Available
  - Non-standard Mounting configurations
- And More - Please inquire for details*

