



Standard Features

- Type 304 Stainless Steel frame, Cover and Fan Guards
- Built-In 0-100° adjustable thermostat
- NEMA 5-15 Plug on 120VAC units
- Standard line cord for other voltages
- Environmentally Friendly - No CFC's, Oils or Gases
- No Maintenance
- Mounts and operates vertically or horizontally
- 12 month warranty
- Made in the USA

Included

- Installation and Operation Manual
- Mounting gasket
- Stainless Steel Mounting Hardware

Standard Voltages

- 120VAC 50/60 Hz
- 240VAC 50/60 Hz
- 24/28VDC

Model #	Available Voltage	Input Voltage Range	Current	Heating Capability	Mounting Flange Dimensions	Certification	Weight	Mounting
AAC-145-4XT-E	120VAC	95-130VAC	6.3 A	N/A	20.25" H X 13" W	ETL to UL 1995	50 LBS.	N/A
	240VAC	190-260VAC	4.6 A					
AAC-145-4XT-E-HC	120VAC	95-130VAC	6.3 A	400 WATTS	20.25" H X 13" W	ETL to UL 1995	50 LBS.	N/A
	240VAC	190-260VAC	4.6 A					
AAC-145-4XT-E-M04	24VDC	23 - 26 V	19 A @24VDC	N/A	20.25" H X 13" W	N/A	50 LBS.	N/A
AAC-145-4XT-E-HC-M04	24VDC	23 - 26 V	19 A @24VDC	400 WATTS	20.25" H X 13" W	N/A	50 LBS.	N/A
AAC-145-4XT-E-M105	120VAC	95-130VAC	6.3 A @ 120VAC	N/A	20.25" H X 13" W	N/A	50 LBS.	N/A
	240VAC	190-260VAC	4.6 A @ 240VAC					
AAC-145-4XT-E-HC-M105	120VAC	95-130VAC	6.3 A @ 120VAC	400 WATTS	20.25" H X 13" W	N/A	50 LBS.	N/A
	240VAC	190-260VAC	4.6 A @ 240VAC					
AAC-145-4XT-E-CE	240VAC	180 - 264VAC	3.5 A @ 240VAC	N/A	20.25" H X 13" W	CE	50 LBS.	N/A
AAC-145-4XT-E-HC-CE	240VAC	180 - 264VAC	3.5 A @ 240VAC	400 WATTS	20.25" H X 13" W	CE	50 LBS.	N/A

1500 BTU - 145 SERIES

THERMOELECTRIC AIR CONDITIONER

NEMA Rating:	4X
Cooling T-Stat set range:	0-100°F
T-Stat Accuracy:	±2°F
T-Stat Hysteresis:	5F
Heating T-stat set point:	ON @ 45F, OFF @ 55F
Cold-side airflow:	230 cfm
Hot-side airflow:	260 cfm
Operating temperature:	-4 to 140 °F
Storage temperature:	-4 to 194 °F
Warranty:	12 months

Optional Equipment

- Condensate Drip Pan
- Extension Frame
- Rain Shroud
- Digital Temperature Controller
- Black Epoxy Coating
- Recessed Frame
- Extended Warranty

Customizations

- Type 316 SS Construction for extreme environments
- Custom color finish
- Increased heating capability
- 12VDC and 48VDC power configuration
- Non-standard Mounting configurations
- And More - Please inquire for details*

