



Standard Features

- Type 304 Stainless Steel frame, Cover and Fan Guards
- Included 0-100° adjustable thermostat
- Terminal Block for easy wiring
- Environmentally Friendly - No CFC's, Oils or Gases
- No Maintenance
- Vertical mounting only
- 12 month warranty
- Made in the USA

Included

- Installation and Operation Manual
- Mounting gasket
- Stainless Steel Mounting Hardware

Standard Voltages

24/28VDC

Model #	Available Voltage	Input Voltage Range	Current	Heating Capability	Mounting Flange Dimensions	Certification	Weight	Mounting
AAC-140-4XT	24/28VDC	23 - 30 V	4/5 A	N/A	7.25" H X 7" W	N/A	12 LBS.	N/A
AAC-140-4XT-HC	24/28VDC	23 - 30 V	4/5 A	100 watts	7.25" H X 7" W	N/A	12 LBS.	N/A

NEMA Rating:	4X
Cooling T-Stat set range:	0-100°F
T-Stat Accuracy:	±1°F
T-Stat Hysteresis:	4F
Heating T-stat set point:	ON @ 45F, OFF @ 55F
Cold-side airflow:	90 cfm
Hot-side airflow:	90 cfm
Operating temperature:	-4 to 140 °F
Storage temperature:	-4 to 194 °F
Warranty:	12 months

Optional Equipment

- Condensate Drip Pan
- Rain Shroud
- Extension Frame
- Digital Temperature Controller
- Black Epoxy Coating
- Recessed Frame
- Extended Warranty

Customizations

- Type 316 SS Construction for extreme environments
- Custom color finish
- Increased heating capability
- 12VDC and 48VDC power configuration
- And More - Please inquire for details*

